

High performance office communication platform

The imageRUNNER ADVANCE C5500i Series delivers high performance and quality colour output for demanding office environments. These intelligent multifunctionals enhance productivity through improved document workflows and intuitive user experience. With added security features, the imageRUNNER ADVANCE C5500i is an essential device for any modern day working environment.



- Intuitive user interface with a large, colour touchscreen provides users with smartphone-like usability, making navigation a breeze.
- Intelligent feeder allows effortless, rapid scanning with features like multi-sheet feed detection and skip blank originals.
- My ADVANCE enables a unique, personal experience tailored to meet each user's workflow needs. Settings, such as display language, initial log-in screen, and accessibility options, can be synchronised across multiple devices for consistency.
- Canon's MEAP platform provides process optimisation, by integrating with a range of powerful document, capture and output management solutions.
- Scalable support for mobile where users can connect directly to the device with Direct Access Point. Capture, scan or print documents easily with the Canon Print Business app.
- Scan and convert documents through a single-pass duplexing document feeder that holds up to 150 originals.
- Intelligent Recovery wakes device from sleep mode when user is approaching device via motion sensor technology.
- Various finishing functions such as Staple-on-Demand, ECO-Staple, saddle stitch, double/corner stapling and foldings are available as an option.

Cost Management

- The ability to apply print policies, monitor output, and restrict usage by user helps reduce unnecessary printing, encourages cost recovery, and can help save money on paper and toner.
- Tight integration with output management solutions, such as uniFLOW, provides the ability to carry out detailed tracking, reporting, and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, can help reduce costs by minimising downtime and time spent by IT resolving issues.
- Consistent user operation combined with remote and centralised fleet management can help simplify IT management of devices and entire fleets.



Security

- Control who has access to the device with Picture Login authentication.
- Prevent unauthorised distribution of sensitive information with an array of standard and optional document security features.
- Ensure information privacy and security across your network with IPsec, port filtering capabilities, and SSL technology.
- Enhance document confidentiality with encrypted secure print, secure print, secure watermark, encrypted PDF and device signature PDF.



Device and Fleet Management Efficiency

- Synchronise personalised user settings across multiple devices through My ADVANCE Sync.
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices remotely, check device and consumables status and capture meter readings.
- Remote diagnostics allow timely, accurate and effective resolution.
- Standard PCL and optional Adobe®
 PostScript® 3™ print driver allows seamless
 integration with enterprise applications.
- Intuitive user maintenance videos and status notifications available to help achieve maximum uptime and keep supplies replenished.

Reliability

- V² (Vivid & Vibrant) imaging technology ensures high quality printouts that impress time after time.
- Supreme transferability of toner and stable reproduction of colours onto a wide range of media, even at large volumes.
- State-of-the-art imaging technologies and toner allow for consistently striking images with real 1,200 dpi, print resolution.
- Maximum paper capacity of 6,350 sheets reduces downtime.

Sustainability

- Fusing technologies, CS toner, and innovative sleep mode features help lower overall energy consumption.
- Minimise paper wastage by holding jobs at the device with Force Hold Print.
 Choose to preview your print jobs or even change print settings at the device to achieve the desired results at the first time of printing.
- Incorporates sustainable design, with the use of recycled materials and biobased plastic, and a focus on minimising environmental impact.
- Consumes as little as 0.8W in sleep mode.

Configuration

BOOKLET FINISHER-Y1

- ·2-tray, 3,250 -sheet capacity
- · Corner and double stapling up to 50 sheets (80 gsm)
- ·Booklet-making up to 20 sheets and nonstaple saddle folded capacity up to 3 sheets (A3/A4R)
- · Supports ECO-Staple 4 sheets (80 gsm) and Staple-on-Demand 50 sheets (90 gsm)
- ·Supports optional internal 2/3 and 2/F4 Hole Puncher Unit-A1



STAPLE FINISHER-Y1

- ·2-tray, 3,250 -sheet capacity
- · Corner and double stapling up to 50 sheets (80 gsm)
- · Supports ECO-Staple 4 sheets (80 gsm) and Staple-on-Demand 50 sheets (90 gsm)
- ·Supports optional internal 2/3 and 2/F4 Hole Puncher Unit-A1





INNER 2 WAY TRAY-J1

- · 2-tray, 350-sheet capacity
- ·Separates copies, prints and faxes
- · Adds a second internal output tray



BUFFER PASS UNIT-L1

- ·Inner tray, 100-sheet capacity
- ·Transports paper to external finisher



INNER FINISHER-H1

- · 2-tray, 545-sheet capacity · Corner and double stapling up to 50 sheets (80 gsm)
- · Supports ECO-Staple 4 sheets (80 gsm) and Staple-on-Demand 40 sheets (80 gsm)
- ·Supports optional Inner 2/3 Hole Puncher-B1 and Inner 2/F4 Hole Puncher –B1





ColorPASS-GX500*

PDL · PS/APPE MEMORY · 4GB/1TB SYSTEM · Fiery FS200 Pro



imagePASS-P1

- ·PCL/PS ·2GB/500GB ·Fiery FS200
- · Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Personalised printing with the built-in, entry-level Fiery FreeForm(TM) or with the supported industry-leading variable data printing (VDP) formats

 Integrates print production workflows with EFI TM
- Integrates print production workflows with EFI IM management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation
- *Applicable to iR-ADV C5550i/C5560i only



CASSETTE FEEDING UNIT-AM1

- ·Supports up to A3
- · Media weight 52-256 gsm
- ·2 x 550 sheets (80 gsm)



HIGH CAPACITY CASSETTE FEEDING UNIT-A1

- ·Supports A4
- · Media weight 52-256 gsm
- ·2,450 sheets (80 gsm)

Main Unit

Type Colour Laser Multifunctional

Core Function

Print, Copy, Scan, Send, Store and Optional Fax

Processor
Canon Dual Custom Processor (Shared)

Control Panel
10.1 inch TFT LCD WSVGA Colour Touchpanel

Memory Standard: 4.0GB RAM

Hard Disk Drive Standard: 250GB Maximum: 1TB

Mirroring Hard Disk Drive Optional 250GB, 1TB

Paper Capacity (80gsm, A4) Standard: 1,200 Sheets Maximum: 6,350 Sheets

Paper Sources (80gsm, A4)
Standard: Two 550-sheet Paper Cassettes
100-sheet Multi-purpose tray
Optional: CASSETTE FEEDING UNIT - AM1:
Two 550-sheet Paper Cassettes
HIGH CAPACITY CASSETTE FEEDING UNIT-A1:
2450 beach Page and Asset Page (2014)

2,450-sheet Paper deck PAPER DECK UNIT-F1: 2,700-sheet Paper deck 6,350 Sheets

Paper Output Capacity (80gsm, A4)

Maximum:

Standard: 250 Sheets
Maximum: 3,450 Sheets (with External Finisher and Copy Tray)

Finishing Capabilities Standard : Collate, Group With Inner : Collate, Group, Offset, Staple, *Hole Punch, Finisher ECO-Staple, Staple-on-Demand

*Requires for INNER 2/3 HOLE PUNCHER-B1 or INNER 2/F4 HOLE PUNCHER-B1

With External: Collate, Group, Offset, Staple, **Booklet, Finisher **Hole Punch, ECO-Staple, Staple-on-Demand *Requires for 2/3 HOLE PUNCHER UNIT-A1 or 2/54 HOLE PUNCHER UNIT-A1

**BOOKLET FINISHER-Y1 only

Supported Media Types
Cassette 1: Thin paper, Plain paper, Thick paper, Colour paper,
Recycled paper, Pre-punched paper, Transparency*,
Bond paper, Envelope, Letterhead

Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency*
Tab paper**, Bond paper, Envelope, Letterhead

CASSETTE FEEDING UNIT-AM1:

Thin paper, Plain paper, Thick paper, Colour paper, Recycled paper, Pre-punched paper, Transparency*, Bond paper, Letterhead

HIGH CAPACITY CASSETTE FEEDING UNIT-A1:
Thin paper, Plain paper, Thick paper, Colour paper,
Recycled paper, Pre-punched paper, Bond paper,
Letterhead

Multi-purpose tray:
Thin paper, Plain paper, Thick paper, Colour paper,
Recycled paper, Pre-punched paper, Transparency*,
Tracing paper, Label, Tab paper, Bond paper,
Coated paper, Envelope, Letterhead, Labels

PAPER DECK UNIT-F1:
Thin paper, Plain paper, Thick paper, Colour paper,
Recycled paper, Pre-punched paper, Bond paper,
Letterhead

· A4 transparencies made especially for multi-functional device •s TAB FEEDING ATTACHMENT F1

Supported Media Sizes
Cassette 1: Standard size: A4, B5, A5, A5R
Envelope : No. 10 (COM10), ISO - C5, DL
Custom Size : 98.0 mm x 148 mm to
297 mm x 215.9 mm

CASSETTE FEEDING UNIT-AM1:
Standard size : A3, B4, A4, A4R, B5, B5R, A5R, Foolscap, India Legal, F4A
Custom size
:98.0 mm x 182 mm to
304.8 mm x 457.2 mm

HIGH CAPACITY CASSETTE FEEDING UNIT-A1:

Standard size : A4
PAPER DECK UNIT-F1 : A4, B5

PAPER DECK UNII-F1

Multi-purpose tray:
Standard size: A3, B4, A4, A4R, B5, B5R, A5, A5R, Foolscap, India Legal, F4A, Envelope (No. 10(COM10), Monarch, DL, ISO-C5)

Custom Size: 98.0 mm x 139.7 mm to 320 mm x 457.2 mm

Free Size: 98.0 mm x 139.7 mm to 320 mm x 457.2 mm

Supported Media Weights
Cassettes : 52 to 256 gsm
Multi-purpose tray : 52 to 300 gsm
Duplex : 52 to 220 gsm

Warm-up Time
*From Power On : 30 Seconds or Less
*Time between device power-on and when the start key is
enabled [print reservation]
From Deep Sleep Mode:10 Seconds or Less

** Quick Startup Mode: 4 seconds
** If <Quick Startup Settings for Main Power> is set to "On", it takes
4 seconds until the key operation on the touch panel display
is available after turning on the main power of the machine.
Depending on the situations, the machine does
not startup quickly.

Dimensions (W x D x H) 620 mm x 742 mm x 950 mm

Installation Space (W x D) 980 mm x 1,176 mm (when Multi-purpose tray Extended + Cassette Drawers open)

Approx. 142kg *Including the toner bottle

Print Specifications

Printing Method Colour laser beam printing

Print Speed iR-ADV C5560i 60 ppm (A4) 32 ppm (A3) 25 ppm (A3) 50 ppm (A4) 32 ppm (A3) 40 ppm (A4) 40 ppm (A4) 40 ppm (A4) 40 ppm (A3) 40 p

Print Resolution 600 dpi x 600 dpi (Default), 1,200 dpi x 1,200 dpi)

Page Description Languages
UFR II, PCL6 (Standard), Adobe PS 3 (Option)

Double Sided Printing Automatic (Standard)

Direct Print
Direct printing available from USB memory key, Advanced
box, Remote UI and Web Access*
Supported Fille Types: PDF, TIFF, JPEG, XPS
*Only PDF print from websites is supported.

Fonts
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T* (Japanese, Korean,
Simplified and Traditional Chinese), Barcode fonts**
*Requires optional PCL INTERNATIONAL FONT SET-A1
**Require optional BARCODE PRINTING KIT-D1
PS fonts: 136 Roman

Operating System
UFRII: Windows Vista/Server 2008/Windows 7/Server 2008 R2/
Server 2012/Windows 8.1/Server 2012 R2/Windows 10/
Server 2016, MAC OS X (10.7 or later)

Windows Vista/Server 2008/Windows 7/Server 2008 R2/ Server 2012/Windows 8.1/Server 2012 R2/Windows 10/ Server 2016

Windows Vista/Server 2008/Windows 7/Server 2008 R2/ Server 2012/Windows 8.1/Server 2012 R2/Windows 10/ Server 2016, MAC OS X (10.7 or later)

MAC OS X (10.3.9 or later), Windows Vista/Windows 7/ Windows8.1/Windows10

Copy Specifications

iR-ADV C5560i: 60 ppm (A4) 32 ppm (A3) iR-ADV C5550i: 50 ppm (A4) 27 ppm (A3) iR-ADV C5540i: 40 ppm (A4) 32 ppm (A3) iR-ADV C5535i: 61 ppm (A4) 18 ppm (A3) Copy Speed iR-ADV C5560i:

*First-Copy-Out Time (A4)
* 20 °C to 30 °C Environment

iR-ADV C5560i: Approx. 2.9 seconds or less (BW) Approx. 4.5 seconds or less (CL) iR-ADV C5550i: Approx. 3.5 seconds or less (BW) Approx. 5.2 seconds or less (CL)

iR-ADV C5540i: Approx. 4.1 seconds or less (BW) Approx. 6.1 seconds or less (CL) iR-ADV C5535i: Approx. 4.9 seconds or less (BW) Approx. 7.4 seconds or less (CL)

Resolution
ing: 600 dpi x 600 dpi
g: Up to 1,200 dpi x 1,200 dpi Copy Res Reading: Printing:

Multiple Copies Up to 999 copies

Copy Exposure Automatic or Manual (9 Levels)

Magnification 25% - 400% (1% Increments)

Preset Reductions 25%, 50%, 61%, 70%, 81%, 86%

Preset Enlargements 115%, 122%, 141%, 200%, 400%

Scan Specifications

Type Single-pass Duplexing Automatic Document Feeder

Document Feeder Paper Capacity 150 Sheets (80gsm)

Document Feeder Supported Media Sizes A3, A4, A4R, A5, A5R, B4, B5, B5R, B6R

*Originals weighing from 38 g/m2 to 42 g/m2 are supp a sinale original that has a width of 257 mm or larger.

Pull Scan Spec Color Network ScanGear2. For both Twain and WIA Supported OS: Windows Vista/7/8.1/10 Windows Server 2008/Server 2008 R2/Server 2012/ Server 2012 R2/ Server 2016

Scan Resolution 100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi

Platen Acceptable Originals Platen: Sheet, Book, 3-Dimensional Objects [Up to 2kg] Feeder size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6

Scan Speed (A4)
Single-sided Scanning (BW) : 80 ipm (300dpi)/80 ipm (600 dpi)
Single-sided Scanning (Colour) : 80 ipm (300dpi)/60 ipm (600 dpi)
Double-sided Scanning (BW) : 160 ipm (300dpi)/150 ipm (600

dpi) Double-sided Scanning (Colour) : 160 ipm (300dpi)/80 ipm (600 dpi)

Double sided scanning 2-sided to 2-sided (Automatic)

Send Specifications

Optional/ standard Standard on all models

Destination E-mail/Internet FAX (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 FAX(Optional), IP Fax(Optional)

Colour Mode Automatic-Colour Select (Full Colour/Grayscale), Automatic-Colour Select (Full Colour/Black-and-White), Full colour, Grayscale, and Black-and-White

LDAP (2,000)/Local (1,600)/One-touch (200)

Send Resolution 100 x 100 dpi, 150 x 150 dpi, 200 x 100 dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi

Communication Protocol File: FTP, SMB v3.0, WebDAV E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

File Format Standard:

TIFF, JPEG, PDF(Compact, Apply policy, Optimize for Web, PDF A/1-b, Encrypted), XPS(Compact), PDF/XPS(Digital Signature)

PDF(Trace&Smooth, Searchable), XPS (Searchable), Office Open XML (PowerPoint, Word) Optional:

Fax Specifications

Optional/ Standard Optional on all models

Maximum Number of Connection Lines 4

Modem Speed Super G3: 33.6 kbps 14.4 kbps

MH, MR, MMR, JBIG Compression Method Resolution 400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi

Sending/Recording Size A5 and A5R* to A3 * Sent as A4

FAX Memory Up to 30,000 pages Speed Dials Max. 200 Group Dials/Destinations Max. 199 dials Seauential Broadcast Max. 256 addresses

Memory Backup

Store Specifications

Mail Box (Number supported) 100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes 30,000 Maximum Pages Stored

Advanced Box
Communication Protocol: SMB or WebDAV
Supported Client PC: Windows (Windows Vista/7/8/8.1/10)
Concurrent Connections (Max.): SMB: 64, WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space Approx. 16GB (Standard HDD) Approx. 480GB (1TB HDD)

Memory Media Standard: USB Memory

Security Specifications

Authentication
Standard: Picture Login Authentication, User Authentication,
Department ID Authentication, (Device and Function
Level Login), Access Management System
Optional: My Print Anywhere secure print (Requires uniFLOW)

Data Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erass, Hard Disk Drive Encryption (FIPS140-2 Validated), Mail Box, Password Protection Optional: Hard Disk Drive Mirrofing, Hard Disk Drive removal

Network Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP

Document Standard: Secure Print, Encrypted PDF, Encrypted Secure Print, Device signature, Secure Watermarks Optional: User signature, Document Scan locking

Environmental Specifications

Operating Environment
Temperature: 10 to 30 °C (50 to 86 °F)
Humidity: 20 to 80 % RH (no condensation)

Power Requirements 220-240V (±10 %) , 50/60Hz (±2 Hz) , 6Amp

Power Consumption Maximum: 1.8 kW Maximum: Standby: Approx. 67.9 W*

*Reference Value Sleep mode: Approx. 0.8 W **

*0.8W sleep mode is not available in all circumstances due to certain settings.

Consumables

Toner Yield (Estimated Yield @5% Coverage) NPG-71 Toner BK : 69,000 Pages NPG-71 Toner C/M/Y : 60,000 Pages

Software and Printer Management

Remote management tools
eMaintenance: Compatible with eMaintenance services via
embedded RDS (Enables meter capture,
automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance)

Content Delivery

iW Management Console:

maintenance)
Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web-based interface to each device that helps to provide remote device management and control.

Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management)

Scanning software

TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device.

Platform
MEAP (Multifunctional Embedded Application Platform): A
powerful JAVA Embedded Platform for Canon devices which
provides tight coupling between a range of software solutions
and the device.

Document Publishing
iW DESKTOP:
Powerful print publishing software which
easily combines documents from different
sources and file formats, applies finishing
with preview and templates to create
professional looking documents. Includes
PDF creation, annotation and compression
capabilities for simple digital workflows such
as proofing and authorization.

Paper Supply Options

PAPER SUPPLYING UNIT
Name:
Paper Capacity:
Paper Size:
CASSETTE FEEDING UNIT-AM1
S50 Sheets x 2 Cassettes (80 gsm)
Standard size: A3, B4, A4, A4R, B5, B5R, A5R,
Foolscop, India Legal, F4A
Custom size:
98.0 mm x 182 mm to
304.8 mm x 457.2 mm
S2 trace/Max

Paper Weight: 52 to 256 gsm
Power Source/Max.
Power Source/Max.
Power Consumption: From the Main Unit
**Dimensions (W x D x H): 620 mm x 700 mm x 251 mm
**When attached with the Min Unit
Weight: Approx. 22.5 kg

HIGH CAPACITY CASSETTE FEEDING UNIT-A1 2,450 sheets (80 gsm)

Name:
Paper Capacity:
Paper Size:
Power Source/Max.
Power Source/Max.
Power Consumption: From the Main Unit
Power Consumption: From the Main Unit
Power Consumption: From the Main Unit
Weight:
Approx. 30 kg

Name: PAPER DECK UNIT-F1 2,700 sheets (80 gsm) A4, B5 52 to 256 gsm

Paper Capacity: Paper Size: Paper Weight:

Power Source/Max.
Power Consumption: From the Main Unit
Dimensions (W x D x H): 344 mm x 630 mm x 440 mm
Weight:
Approx. 31 kg

Output options

INNER FINISHER

Name: Number of Trays:

A4/B5/A5/A5R 45 sheets Top Tray Capacity:

A3/B4/A4R/B5R 45 sheets A4/B5/A5/A5R 500 sheets Lower Tray Capacity: A3/B4/A4R/B5R 250 sheets Paper Weight: 52 to 300 gsm Corner, Double

INNER FINISHER-H1

Staple Position:
Staple Capacity:
Corner and Double
Stapling: ECO-Staple:

A4/B5: 50 sheets (52 to 90 gsm)
A3/B4/A4R: 30 sheets (52 to 90 gsm)
A3/A4/B4/B5: 5 sheets (52 to 64 gsm)
A sheets (65 to 81.4 gsm)
A sheets (65 to 81.4 gsm)

Staple-on-Demand: 40 sheets (80 gsm)

Power Source/Max. Power Consumption: Dimensions (WxDxH): Weight:

From the Main Unit 466 mm × 525 mm × 225 mm Approx. 8.6 kg

STAPLE FINISHER-Y1 (External)

STAPLE FINISHER Name: Number of Trays:

A4/B5/A5/A5R 250 sheets A3/B4/A4R/B5R 125 sheets A4/B5/A5/A5R 3,000 sheets A3/B4/A4R/B5R 1,500 sheets Top Tray Capacity: Lower Tray Capacity:

Paper Weight: Upper Tray 52 to 256 gsm Lower Tray 52 to 300 gsm Staple Position: Corner, Double

Staple Capacity: Corner and Double Stapling:

ECO-Staple:

A4/B5: 50 sheets (52 to 90 gsm) A3/B4/A4R: 30 sheets (52 to 90 gsm) A3/A4: 5 sheets (52 to 64 gsm) A3 sheets (65 to 81.4 gsm) 3 sheets (81.5 to 105 gsm)

Staple-on-Demand: 50 sheets (90 gsm)
*Dimensions (W x D x H): 637 mm × 623 mm × 1,142 mm

Approx. 31 kg Weight:

BOOKLET FINISHER BOOKLET FINISHER-Y1 (External) Number of Trays:

A4/B5/A5/A5R 250 sheets A3/B4/A4R/B5R 125 sheets Top Tray Capacity: A4/B5/A5/A5R 3,000 sheets A3/B4/A4R/B5R 1,500 sheets Upper Tray 52 to 256 gsm Lower Tray 52 to 300 gsm Lower Tray Capacity: Paper Weight: Corner Double

Staple Position: Staple Capacity: Corner and Double Stapling:

Booklet Stitch paper Booklet Stitch Staple

50 sheets (40 gsm)
A3/B4/A4R, Custom Size
(195 mm x 270 mm to
304.8 mm x 457.2 mm)
20 sheets x 10 sets (52-81.4gsm)
(Including 1 cover sheet up to 256 gsm)
637 mm × 632 mm x 1,142 mm
*When the extension tray is extended Capacity:
*Dimensions (WxDxH): Approx. 57 kg

Weight:

PUNCHER UNIT/S INNER 2/3 HOLE PUNCHER-B1:

Acceptable Punch Paper Weight:

Acceptable Punch Paper Size:

Power Source:

INNER 2/F4 HOLE PUNCHER-B1: Acceptable Punch Paper Weight:

Acceptable Punch Paper Size: Power Source:

Two or Three Holes
*Requires INNER FINISHER-H1

52 to 300 gsm

Two holes A3, B4, A4, A4R, B5, B5R Three holes A3, B4, A4, B5 From the Main Unit

Two or Four Holes Requires INNER FINISHER-H1 52 to 300 gsm

Two holes A3, B4, A4, A4R, B5, B5R Four holes A3, A4 From the Main Unit

2/3 HOLE PUNCHER-A1:

Two or Three Holes *Requires either the STAPLE FINISHER-Y1 or BOOKLET FINISHER-Y1

Acceptable Punch Paper Weight: Acceptable Punch Paper Size: 52 to 300 gsm

Two holes A3, B4, A4, A4R, B5, B5R Three holes A3, B4, A4, B5 From the Main Unit Two or Four Holes *Requires either the STAPLE FINISHER-Y1 or BOOKLET

Power Source: 2/F4 HOLE PUNCHER-A1: FINISHER-Y1

Acceptable Punch Paper Weight: Acceptable Punch Paper Size:

Power Source

52 to 300 gsm

Two holes A3, B4, A4, A4R, B5, B5R Four holes A3, A4 From the Main Unit

Hardware Accessories

Card Readers MICARD PLUS PROXIMITY CARD READER COPY CARD READER-F1 COPY CARD READER ATTACHMENT-B5

TAB FEEDING ATTACHMENT KIT-F1 UTILITY TRAY-B1 INNER 2WAY TRAY-J1

Security Options

DOCUMENT SCAN LOCK KIT-B1

Data Security HDD MIRRORING KIT-J1 2.5INCH/250GB HDD-N1 2.5INCH/1TB HDD-P1 REMOVABLE HDD KIT-AL 1

System and Controller options

Print Accessories PCL INTERNATIONAL FONT SET-A1 PCL ASIAN FONT SET-A1

Barcode Printing BARCODE PRINTING KIT-D1

EFI-Fiery Based Controller IMAGEPASS-P1 COLOURPASS-GX500 (Applicable for iR-ADV C5550i/C5560i only)

EFI-Fiery Based Controller Options REMOVABLE HIDD DRIVE KIT-B1 FIERY IMPOSE FIERY COMPOSE FIERY IMPOSE AND COMPOSE

System Accessories SERIAL INTERFACE KIT-K3

FAX Accessories SUPER G3 FAX BOARD-AS1 SUPER G3 SVD LINE FAX BOARD-AS1 SUPER G3 SRD/4TH LINE FAX BOARD-AS1 REMOTE FAX KIT-A1 IP FAX EXPANSION KIT-B1

Other Options

Accessibility Accessories ADF ACCESS HANDLE-A1 VOICE GUIDANCE KIT-G1 VOICE OPERATION KIT-D1

Consumables STAMP INK CARTRIDGE-C1 STAPLE-P1 STAPLE CARTRIDGE-Y1









0211W184 @ 2018 Canon Singapore Pte. Ltd. All rights reserved. Printed in Singapore.



To arrange for a demonstration, simply contact our office below.

SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS

Canon Singapore Pte. Ltd. 1 Fusionopolis Place #15-01 Galaxis Singapore 138522

Tel: 65-6799 8888 Fax: 65-6799-8882 www.canon-asia.com www.canon.com.sa

Partner / Dealer Stamp

This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document.

Canon, imageRUNNER, imageRUNNER ADVANCE, imageCHIP, RAPID Fusing System, MEAP, eMaintenance, tW, Business can be simple and get Smart get genuine are trademarks of Canon linc, and/or its affiliates. "MEAP" is a trademark of CANON linc, referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners.