

High productivity, compact A4 device with intelligent and secure features

The imageRUNNER ADVANCE 715iZ/615i III is designed for busy work groups who require compact and secure solutions.

WORKFLOW EFFICIENCY

- Intuitive touchscreen provides users with smartphone-like usability, making navigation a breeze.
- Intelligent feeder allows effortless, rapid scanning with features like multi-sheet feed detection and skip blank originals.
- My ADVANCE enables a unique, personal experience tailored to meet each user's workflow needs. Settings, such as display language, initial log-in screen, and accessibility options, can be synchronised across multiple devices for consistency.
- Canon's MEAP platform provides process optimisation, by integrating with a range of powerful document, capture and output management solutions.
- Scalable support for mobile where users can connect directly to the device with Direct Access Point. Capture, scan or print documents easily with the Canon Print Business app.
- Intelligent Recovery wakes device from sleep mode when user is approaching device via motion sensor technology.

COST MANAGEMENT

- The ability to apply print policies, monitor output, and restrict usage by user helps reduce unnecessary printing, resulting in lower total document cost.
- Tight integration with output management solutions, such as uniFLOW, provides the ability to carry out detailed tracking, reporting, and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, can help reduce costs by minimising downtime and time spent by IT resolving issues.
- Consistent user operation combined with remote and centralised fleet management can help simplify IT management of devices and entire fleets.



SECURITY

- Control who has access to the device with different authentication methods such as picture login, department ID, user authentication and card access.
- Ensure information privacy and security across your network with IPsec, port filtering capabilities, and SSL technology.
- Enhance document confidentiality with encrypted secure print, secure print, secure watermark, encrypted PDF and device signature PDF.
- Ensure device is safe from unknown firmware installation with system verification at startup.
- Integrate with third-party solutions for complete monitoring protection.

QUALITY AND RELIABILITY

- The new All-in-One cartridge makes replacement easy and convenient, increasing device uptime.
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices remotely, check device and consumables status and capture meter readings.
- Standard PCL and Adobe® PostScript™ print driver allows seamless integration with enterprise applications.
- Remote diagnostics allow timely, accurate and effective resolution.
- Intuitive user maintenance videos and status notifications available to help achieve maximum uptime and keep supplies replenished.

SUSTAINABILITY

- Combination of fusing technologies and low-melting-point toner help lower overall electricity.
- Minimise paper waste by holding jobs at the device with Force Hold Print. Choose to preview your print jobs or even change print settings at the device to achieve the desired results at the first time of printing.

PRODUCT SPECIFICATION

iR-ADV 615i III



iR-ADV 715iZ III (Finisher Model)



CASSETTE FEEDING UNIT-AR1



HIGH CAPACITY CASSETTE FEEDING UNIT-D1



CASSETTE MODULE-AG1
ENVELOPE CASSETTE MODULE-A1

MAIN UNIT

Type

A4 Monochrome Laser Multifunctional

Core Function

Print, Copy, Scan, Send and Optional Fax

Processor

Canon Dual Custom Processor (Shared)

Control Panel

10.1 inch WSVGA Colour Touch panel

Memory

Standard: 3.0GB RAM

Hard Disk Drive

Standard: 250GB

Interface Connection

Network Standard: 100Base-T/100Base-TX/10Base-T,
Wireless LAN (IEEE 802.11 b/g/n)

Optional : NFC, Bluetooth Low Energy

Others

Standard : USB 2.0 x2 (Host), USB 3.0 x1 (Host),
USB 2.0 x1 (Device)

Optional : Copy Control Interface

Paper Supply Capacity (A4, 80gsm)

Standard : 650 Sheets (1 x 550-sheet cassette, 100-sheet
multi-purpose tray)

Maximum : 3,300 Sheets*

(with High Capacity Cassette Feeding Unit-D1)

Paper Output Capacity (A4, 80gsm)

iR-ADV 615i III : 500 Sheets

iR-ADV 715iZ III : 1,000 Sheets

Finishing Capabilities

iR-ADV 615i III : Collate, Group

iR-ADV 715iZ III : Collate, Group, Offset*, Staple

*available with upper tray

Supported Media Types

Paper Cassette:

Thin, Plain, Recycled, Thick, Colour, Labels, Bond, Pre-punched

Multi-Purpose Tray:

Thin, Plain, Recycled, Thick, Colour, Transparency, Bond,
Envelope

Supported Media Sizes

Paper Cassette:

Standard size: A4, A5, A5R, A6, B5

Custom Size: 99.0 x 148.0 mm to 215.9 x 297.0 mm

Multi-Purpose Tray:

Standard size: A4, A5, A5R, A6, B5, Envelope[No.10
(COM10)], Monarch, DL, ISO-C5]

Custom Size: 76.2 x 127.0 mm to 215.9 x 355.6 mm

Supported Media Weights

Cassettes : 60 to 135 gsm

Multi-purpose tray : 60 to 199 gsm

Duplex : 60 to 120 gsm

Warm-up Time

From Power On : 24 Seconds or Less**

From Deep Sleep Mode: 10 Seconds or Less

Quick Startup Mode : 4 seconds or Less**

*1 Time from device power-on to when key operations can be performed
on the touch panel display.

Dimensions (W x D x H)

iR-ADV 615i III : 513 x 601 x 617 mm

iR-ADV 715iZ III : 515 x 601 x 814 mm

Installation Space (W x D)

iR-ADV 615i/715iZ III: 1052 x 823mm

(with left CRG door, right door and cassette drawer open)

Weight including the toner

iR-ADV 615i III : Approx. 37 kg (including toner)

iR-ADV 715iZ III : Approx. 46 kg (including toner)

Print Specifications

Print Speed (ppm)

iR-ADV 715iZ III : up to 71 (A4), up to 113 (A5), up to 40 (A5R)

iR-ADV 615i III : up to 61 (A4), up to 99 (A5), up to 35 (A5R)

Print Resolution (dpi)

Data processing resolution: 600 x 600 (default),
1,200 x 1,200 (up to)

Page Description Languages

Standard: UFR II, PCL6, PS 3

Direct Print

Direct printing available from USB memory, Advanced box,
Remote UI and Web Access**

Supported File Types: PDF, TIFF, JPEG, XPS, EPS

**Only PDF print from websites is supported.

Printing From Mobile and Cloud

AirPrint, Mopria, Google Cloud Print, and Canon Print Business
and uniFLOW Online

Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T* (Japanese, Korean,
Simplified and Traditional Chinese),
Barcode fonts**

PS fonts: 136 Roman

*1 Requires optional PCL INTERNATIONAL FONT SET-A1

*2 Require optional BARCODE PRINTING KIT-D1

Operating System

UFR II: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server
2012/Server 2012 R2/Server 2016, MAC OS X (10.9 or later)

PCL: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server
2012/Server 2012 R2/Server 2016

PS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server
2012/Server 2012 R2/Server 2016, MAC OS X (10.9 or later)

PPD: MAC OS X (10.3.9 or later), Windows® 7/8.1/10

Copy Specifications

Copy Speed (Simplex, BW)

iR-ADV 715iZ III : up to 71 (A4), up to 113 (A5), up to 40 (A5R)

iR-ADV 615i III : up to 61 (A4), up to 99 (A5), up to 35 (A5R)

Copy Resolution (dpi)

Reading : 600 x 600

First-Copy-Out Time (A4): Approx. 5 seconds or less

Multiple Copies

Up to 9,999 copies

Copy Density

Automatic or Manual (9 Levels)

Magnification

25% - 400% (1% Increments)

Preset Reductions

25%, 50%, 70%, 81%, 86%

Preset Enlargements

115%, 122%, 141%, 200%, 400%

Scan Specifications

Standard Type

Single-pass Duplexing Automatic Document Feeder [2-sided
to 2-sided (Automatic)]

Document Feeder Paper Capacity (80gsm)

100 Sheets

Acceptable Originals and Weights

Platen: Sheet, Book, 3-Dimensional Objects
(Height: up to 30 mm, Weight: up to 2kg)

Document Feeder: Sheet media weight:

42 to 128 gsm/64 to 128 gsm (BW/CL) *

*A6: 52 gsm to 128 gsm/64 to 128 gsm (BW/CL)

Supported Media Sizes

Platen: max. scanning size: 216.0 x 355.6 mm

Document Feeder media size:

A4, A5, A6, B5 , Custom size: 105.0 x 148.0 mm to

216.0 x 355.6 mm

Scan Speed (A4, BW/CL)

1-sided Scanning: 50 ipm/50 ipm (300dpi, Send),
50ipm/- (600dpi, Copy)

2-sided Scanning: 100 ipm/100 ipm (300dpi, Send),
100ipm/- (600dpi, Copy)

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,
200 x 100, 150 x 150, 100 x 100

Pull Scan Spec

Colour Network ScanGear2. For both Twain and WIA

Supported OS: Windows 7/8.1/10/Server 2008/Server 2008
R2/Server 2012/Server 2012 R2/Server 2016

Send Specifications

Destination

E-mail/Internet FAX (SMTP), SMB v3.0, FTP, WebDAV, Mail Box,
Super G3 FAX(Optional), IP Fax(Optional)

Address Book

LDAP (2,000)/Local (1,600)/One-touch (200)

Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,
200 x 100, 150 x 150, 100 x 100

Communication Protocol

File : FTP (TCP/IP), SMB v3.0 , WebDAV

E-mail/I-Fax : SMTP, POP3

File Format

Standard : TIFF, JPEG, PDF(Compact, Apply policy,
Optimize for Web, PDF A/1-b, Encrypted,
Device Signature), XPS(Compact, Device
Signature)

Optional : PDF(Trace & Smooth, Searchable, User
Signature), XPS(Searchable, User Signature),
Office Open XML (PowerPoint, Word)

Fax Specifications

Maximum Number of Connection Lines 1

Modem Speed Super G3 : 33.6 kbps
G3 : 14.4 kbps

Compression Method MH, MR, MMR, JBIG

Resolution (dpi) 400 x 400, 200 x 400, 200 x 200,
200 x 100

Sending/Recording Size A4, A5*, A6* and B5*
* Sent as A4

FAX Memory Up to 30,000 pages

Speed Dials Max. 200

Group Dials/Destinations Max. 199 dials

Sequential Broadcast Max. 256 addresses

Memory Backup Yes

Store Specifications

Mail Box (Number supported)

100 User Inboxes, 1 Memory RX Inbox,

50 Confidential Fax Inboxes

30,000 Maximum Pages Stored

Advanced Box

Communication Protocol: SMB or WebDAV

Supported Client PC: Windows (Windows 7/8.1/10)

Concurrent Connections (Max.): SMB: 64, WebDAV:
3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16GB (Standard HDD)

Memory Media

Standard: USB Memory

Security Specifications

Authentication

Standard : User Authentication (Picture Login/Keyboard
Authentication), DepartmentID Authentication,
Access Management System

Optional: My Print Anywhere secure print (Requires
uniFLOW), uniFLOW Online Express Cloud based
management software

Data

Standard: Trusted Platform Module (TPM), Hard Disk
Password Lock, Hard Disk Drive Erase, Mail Box
Password Protection, Hard Disk Drive
Encryption (FIPS140-2 Validated)

Optional : IEEE 2600 Common Criteria Certification, Data
Loss Prevention (Requires uniFLOW and iWSAM
Express)

Network

Standard : IP/Mac Address Filtering, IPSEC, TLS Encrypted
Communication, SNMP V3.0, IEEE 802.1X,
IPv6, SMTP Authentication, POP Authentication
before SMTP, S/MIME

Document

Standard : Secure Print, Adobe LiveCycle® Rights
Management ES2.5 Integration, Encrypted PDF,
Encrypted Secure Print, Device Signature, Secure
Watermarks

Optional : User Signature

Environmental Specifications

Operating Environment

Temperature: 10 to 30 °C

Humidity: 20 to 80 % RH (Relative Humidity)

Power Source 220-240V (±10 %), 50/60Hz (±2 Hz), 4.8Amp

Power Consumption

Maximum: Approx 1,500W

Printing: 749.7 W¹ (iR-ADV 715iZ III),

717.7 W¹ (iR-ADV 615i III)

Standby: Approx. 29.53 W¹

Sleep mode: Approx. 1.0 W

*1 Reference Value (measured one unit)

Consumables

Toner T03 Black

Toner Yield

Black: 51,500 pages (A4)

Toner Cartridge yield in accordance with ISO/IEC 19752

Software and Printer Management

Tracking and Reporting

Universal Login Manager (ULM): Manage your costs easily by using the embedded reporting capability to identify and control costs on a user-based level by device.

uniFLOW Online Express: Combining with ULM you can gain further control, highlight expenditures per users/department and pinpoint where costs can be scaled down from a central cloud based location.

Remote management tools

iW Management Console: Server-based software for centralised management of a fleet of devices (includes monitoring of consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management)

eMaintenance: Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance)

Content Delivery System: Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web-based interface to each device that helps to provide remote device management and control.

Scanning software

Network ScanGear: TWIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device.

Optimisation Tools

Canon Driver Configuration Tool: A utility for changing the factory default settings of Canon print drivers

NetSpot Device Installer: Simple utility software that allows you to make network protocol settings for Canon devices connected to your network.

Platform

MEAP (Multifunctional Embedded Application Platform): A powerful JAVA Embedded Platform for Canon devices which provides tight coupling between a range of software solutions and the device.

MEAP Web: Web service alternative to MEAP that allows MFP applications to be developed and deployed via web services.

Paper Supply Options

CASSETTE FEEDING UNIT-AR1

Paper Capacity	: 550 Sheets (80gsm)
Paper Size	: A4, A5, A5R, A6, B5,
Custom size	: 99 x 148 mm to 215.9 x 355.6 mm
Paper Type	: Thin, Plain, Recycled, Thick, Colour, Labels, Bond, Pre-punched
Paper Weight	: 60 to 135 gsm
Power Source	: From the Main Unit
Dimensions (WxDxH)	: 642 x 657 x 456 mm (attached to main unit)
Weight	: Approx. 19 kg

HIGH CAPACITY CASSETTE FEEDING UNIT-D1

UPPER CASSETTE	
Paper Capacity	: 550 sheets (80 gsm)
Paper Size	: A4, A5, A5R, A6, B5, Custom size: 99 x 148 mm to 215.9 x 355.6 mm
Paper Type	: Thin, Plain, Recycled, Thick, Colour, Labels, Bond, Pre-punched
Paper Weight	: 60 to 135 gsm

LOWER CASSETTE

Paper Capacity	: 2,100 sheets (80 gsm)
Paper Size	: A4
Paper Type	: Thin, Plain, Recycled, Thick, Colour, Bond, Pre-punched
Paper Weight	: 60 to 135 gsm
Power Source	: From the Main Unit
Dimensions (WxDxH)	: 642 x 657 x 456 mm (attached to main unit)
Weight	: Approx. 25 kg

CASSETTE MODULE-AG1

Paper Capacity	: 550 Sheets (80 gsm)
Paper Size	: A4, A5, A5R, A6, B5, Custom size: 99 x 148 mm to 215.9 x 355.6 mm
Paper Type	: Thin, Plain, Recycled, Thick, Colour, Labels, Bond, Pre-punched
Paper Weight	: 60 to 135 gsm
Power Source	: From the Main Unit
Dimensions (W x D x H)	: 484 x 450 x 127 mm (attached to main unit)
Weight	: Approx. 7 kg

ENVELOPE CASSETTE MODULE-A1

Paper Capacity	: 75 sheets (Envelope)
Envelope Size	: COM10 (No.10), Monarch, DL, ISO-C5
Paper Weight	: 80 to 100 gsm
Power Source	: From the Main Unit
Dimensions (W x D x H)	: 484 x 450 x 127 mm (attached to main unit)
Weight	: Approx. 7 kg

Output Features

iR-ADV 715iZ III

Number of Inner Trays	: 2
Upper Tray Capacity	: A4, A5, B5, Custom size (148 x 210 mm to 215.9 x 355.6 mm): 400 sheets
Lower Tray Capacity	: A4, A5, B5, Custom size (148 x 210 mm to 215.9 x 355.6 mm): 100 sheets
Main unit output tray (80gsm)	: 500 sheets
Paper Type	: Thin, Plain, Recycled, Thick, Colour, Bond
Staple Paper Weight	: 60 to 120 gsm
Staple Paper Size	: A4, Custom size (210.0 x 279.4 mm to 215.9 x 355.6 mm)
Staple Position	: Corner
Staple Capacity	: 30 sheets (60-90gsm), 20 sheets (91-120gsm)

Hardware Accessories

Card Readers

COPY CARD READER-F1
COPY CARD READER ATTACHMENT-B5

Security Options

Document Security

IR-ADV SECURITY KIT-AF1

System and Controller Options

Print Accessories

PCL INTERNATIONAL FONT SET-A1
PCL ASIAN FONT SET-A1

Send Options

UNIVERSAL SEND ADVANCED FEATURE SET-H1
UNIVERSAL SEND DIGITAL USER SIGNATURE KIT-C1

Barcode Printing

BARCODE PRINTING KIT-D1

System Accessories

COPY CONTROL INTERFACE KIT-A1
NFC KIT-C1
BLE CONNECTION KIT-A1

Fax Accessories

SUPER G3 FAX BOARD-AY1
REMOTE FAX KIT-A1
IP FAX EXPANSION KIT-B1

Other Options

Accessibility Accessories

ADF ACCESS HANDLE-A1

Staple Cartridge

STAPLE-P1



Partner / Dealer Stamp

To arrange for a demonstration, simply contact any of our offices below.

SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS

Canon Singapore Pte. Ltd.

1 Fusionopolis Place

#15-01 Galaxis Singapore 138522

Tel : 65-6799 8888

www.canon-asia.com

Fax : 65-6799-8882

www.canon.com.sg